



“Our ATSI SCADA system costs \$55,000 to put in, and the first year alone, we saved \$42,000 in energy costs. Time of Use Pumping Operation has saved thousands of dollars during the peak energy billing periods of summer.”

**Ventura River County
Water District**

U.S.A.
CSE Semaphore Inc.
1200 Chantry Place
Lake Mary, FL 32746
U.S.A.

P +1 (407) 333 3235
F +1 (407) 386 6284

Australia
CSE-Semaphore
Unit 8, 3-5 Gilda Crt
Mulgrave, Victoria 3170
Australia

P +61 (03) 8544 8544
F +61 (03) 8544 8555

Europe
CSE-Semaphore Begium
Waterloo Office Park — Building “M”
Dreve Richelle, 161
B-1410 Waterloo
Belgium

P +32 (2) 387 42 59
F +32 (2) 387 42 75

© 2007 CSE-Semaphore. All rights reserved. T-BOX, T-VIEW, and Dream Report are trademarks of CSE-Semaphore. All other marks may be trademarks of their respective owners. 0761023 10/07

Kingfisher RTUs Installed in Ventura River County Water System

When the Ventura River County Water District in Ojai, California, required a new SCADA system, the solution was an ATSI Intelligent SCADA system utilizing Kingfisher RTUs.

The system was designed with Distributed Control architecture to provide “fail-safe” operation and to minimize the impact of single and multiple component failures during system operation. The SCADA computer is updated with data to accurately display field conditions, while also allowing operators to transmit new set-points to the field RTUs. In addition, the computer is no longer a critical piece of system operation.

PC-programmable radio modems (2-watt UHF, 9600 bit/sec) transmit data in a peer-to-peer network across the system. The configuration of the radio network is accomplished in ATSI SCADA RTUs. Operationally, the SCADA system automatically controls and monitors the following parameters:

- Reservoir levels and level trending
- Well water levels
- Well/booster flow and total
- Booster/well call (start/stop)
- Booster/well status (running/off/fail)
- Booster/well run time and number starts
- RTU communications status
- RTU back-up battery status
- Power status
- Real-time and historical trending

System alarms are uniquely handled

Not wanting a computer to have the ultimate destiny in the dispatch of very necessary system alarms, the customer elected to use the ATSI RTU Alphanumeric Paging functions built into the RTU/FEP firmware. If computer operation is halted for any reason, the ATSI Front-End Processor RTU still sends the alarm information to field maintenance personnel via Alphanumeric Paging. This has proven to be highly reliable and effective in the transmitting of alarms.

Reports are generated automatically based upon data collected from field devices. This provides the necessary information for compliance with local, state, and federal agency reporting requirements. In addition to being stored on the hard disk drive, data is also exported to a 100 megabyte drive for archival storage. The SCADA system features Remote Access for remote viewing of system display screens as well as remote access to the ladder logic running in field RTUs. Any RTU may have its logic checked or changed over radio links, even from remote locations.